1-22-025 / GNEx: GRP explosion/flameproof

# GNExS2H Alarm Horn Sounder

**The GNExS2H is a very high output 127dB(A) IECEx and ATEX certified alarm horn sounder featuring an enhanced re-entrant flare horn. The robust GRP (glass reinforced polyester) enclosure is approved for Zone 1 & Zone 2 explosion proof signalling applications.**

Featuring 64 alarm tone sounds, each of the available 4 stage/channels can be remotely triggered. Class D amplification provides a high sound output with a choice of two power modes. The threaded flameproof joint, multiple cable entries and duplicated, pluggable termination simplifies both installation and routine maintenance. SIL1 & SIL2 Route 2H compliant to IEC61508 (2010) as standard.

## Features

- Maximum sound pressure level output of 126dB(A)
- Choice of 64 alarm tone frequencies
- 4 remotely selectable alarm stages/channels
- Positive or negative line stage/channel switching
- Automatic synchronisation on multi-sounder system
- Ratchet adjustable 316 stainless steel bracket
- Triple cable entries
- Available with custom tone configurations and frequencies
- Robust corrosion proof GRP (glass reinforced polyester) enclosure



## Approvals

- ATEX certificate: SIRA 13ATEX1139X
- IECEx certificate: IECEx SIR 13.0029X
- UL certificate: E549307
- TR-CU Ex EAC certificate: RU C-GB.AA71.B.00109
- INMETRO IEx 20.0050X
- SIL1 & SIL2 compliant to IEC61508 (2010)

## Coding

- IECEx / ATEX
  II 2G Ex d IIC T4 Ta. -60°C to +50°C
  II 2G Ex d IIC T3 Ta. -60°C to +58°C
  II 2G Ex d IIB T6 Ta. -60°C to +50°C
  II 2G Ex d IIB T5 Ta. -60°C to +58°C



## Specification

| | |
|---|---|
| Maximum output: | High power level: 127dB(A) @ 1 m +/- 3dB [118dB(A) @ 10ft/3m +/- 3dB]<br>Medium power level: 122dB(A) @ 1 m +/- 3dB [113dB(A) @ 10ft/3m +/- 3dB] |
| Nominal output: | High power level: 124dB(A) @ 1m +/- 3dB [115dB(A) @ 10ft/3m] +/- 3dB<br>Medium power level: 119dB(A) @ 1m +/- 3dB [110dB(A) @ 10ft/3m] +/- 3dB |
| No. of tones: | 64 (UKOOA / PFEER compliant) |
| No. of stages: | 4 |
| Volume control: | Full range |
| Effective range: | >350m/1148ft @ 1KHz |
| Voltages DC: | 24Vdc (10-30vdc), 48vdc (38-60Vdc) |
| Voltages AC: | 230Vac (100-260Vac) |
| In-rush: | 815mA within 4ms @ 24Vdc |
| Stage switching: | DC units: positive or negative<br>AC units: common supply line |
| Safety Integrity Level: | SIL1 and SIL2 Route 2H IEC61508 (2010) |
| Ingress protection: | EN60529: IP66 |
| Enclosure material: | UV stable GRP (glass reinforced polyester) |
| Enclosure colour: | Natural Red |
| Enclosure finish: | Natural – can be painted in alternative colours |
| Cable entries: | 2 x M20x1.5mm<br>Stopping plug included |
| Stopping plugs: | Brass, Nickel Plated or Stainless Steel |
| Terminals: | 0.5 – 2.5mm² (20-14 AWG)<br>Pluggable & duplicated terminals |
| Line monitoring: | Diode polarized for use in supervised circuits<br>Blocking diode for reverse polarity monitoring |
| Ground/Earth stud: | M4 |
| Line monitoring: | Blocking diode included<br>EOL Min. 500 Ohm 2W, or 3k3 Ohm 0.5W resistor or diode (DC versions) can be fitted |
| Enclosure volume: | <2 litres |
| Installation temp: | -50° to +70°C (-58°F to +158°F) |
| Storage temp: | -50° to +70°C (-58°F to +158°F) |
| Relative humidity: | 99% |
| MTBF DC: | 93.92 years / 822,706 hours – MIL 217 |
| MTBF AC: | 46.66 years / 408,508 hours – MIL 217 |
| Weight: | DC: 3.00kg/6.6lbs AC: 3.20kg/7.04lbs |

## Part Codes

| Part Code: | Identifier: | Description: |
|---|---|---|
| Product type: | GNExS2 | GNExS2 alarm horn sounder |
| Horn type: | H | High SPL flare re-entrant horn |
| Voltage: | DC024 | 10-30Vdc |
| | DC048 | 38-60Vdc |
| | AC230 | 100-260Vac |
| Cable entries:[e] | A | 3 x M20x1.5mm |
| | B | 2 × 1/2" NPT – adaptors |
| | C | 2 × 3/4" NPT – adaptors |
| | D | 2 x M25x1.5mm – adaptors |
| | E | 1 × 1/2" NPT – adaptor |
| | F | 1 × 3/4" NPT – adaptor |
| | G | 1 x M25x1.5mm – adaptor |
| Stopping plug/ adaptor material: [m] | B | Brass |
| | N | Nickel plated brass |
| | S | Stainless steel |
| Bracket material: [s] | 1 | A4 316 Stainless Steel |
| | 3 | A4 316 St/St with Equip. Tag |
| Product version: [v] | A | IECEx, ATEX, UL, Ex EAC, INMETRO SIL1 & SIL2 Route 2H |
| | S | IECEx, ATEX, UL, Ex EAC, INMETRO SIL2 Route 1H with diagnostics SFF: >99% |
| | T | IECEx, ATEX, Ex EAC, INMETRO – Telephone/Relay initiate |
| Product option: [o] | 1 | Standard product |
| | Z | Custom alarm tone software – contact E2S |
| | X | Custom configuration – contact E2S |
| | Y | Stage control Config. 4 |
| | K | Stage control Config. 5 (DC) and Config. 2 (AC) |
| | V | Stage control Config. 6 |
| Enclosure colour: [x] | R | Red |
| | S | Special – contact E2S for alternative enclosure colours |

**Accessories:**

| | |
|---|---|
| SP65-0001-A4 | Pole Mount Bracket Kit St/St A4 (316) |


**Alarm stage control:**

Please review the installation manual and wiring schematics for remote stage control and EOL resistor monitoring configuration options:

| | |
|---|---|
| Config. 1 [DC]: | Factory default. Common negative, positive switching. Up to 4 Alarm Stages. EOL monitoring Alarm Stage 1 only |
| Config. 2 [DC]: | User setting. Common positive, negative switching. Up to 4 Alarm Stages. EOL monitoring Alarm Stage 1 only |
| Config. 3 [DC]: | User setting. Common negative, positive switching activation of Alarm Stages 1 & 2 with EOL on both stages. Reverse polarity monitoring |
| Config. 4 [DC]: | Product option 'Y'. Independent activation of Alarm Stages 1 & 2 with EOL on both stages. Forward polarity monitoring |
| Config. 5 [DC]: | Product option 'K'. Horn continuously powered. Voltage free activation of up to 3 alarm stages |
| Config. 6 [DC]: | Product option 'V'. Independent activation of up to 4 Alarm Stages with EOL on all stages. Forward polarity monitoring |
| Config. 1 [AC]: | Factory default. Up to 4 Alarm Stages. Stage 1 activated at power on. Stages 2, 3 and 4 via volt free contacts |
| Config. 2 [AC]: | Product option 'K'. Horn continuously powered. Voltage free activation of up to 3 alarm stages |

## Current Consumption

| Nominal Voltage: | Voltage range: | Medium Power current: | Medium Power Max. Current: | High Power current: | High Power Max. Current: | In-rush: |
|---|---|---|---|---|---|---|
| 12Vdc | 10-30Vdc | 289mA | 324mA | 356mA | 740mA | - |
| 24Vdc | 10-30Vdc | 324mA | 324mA | 740mA | 740mA | 815mA <4ms |
| 48Vdc | 38-60Vdc | 195mA | 195mA | 391mA | 391mA | - |
| 115Vac 50/60Hz | 100-260V ac | 125mA | 138mA | 282mA | 325mA | - |
| 230Vac 50/60Hz | 100-260V ac | 78mA | 138mA | 167mA | 325mA | - |




## Assemblies

The GNExS2H is available as a plated assembly configured with Xenon strobe or LED beacons with or without a GNExJ2 Ex d junction box.

Contact E2S for further information.

## Tone table

| S 1 | Description | S 2 | S 3 | S 4 |
|---|---|---|---|---|
| T 1 | 1000 Continuous - PFEER Toxic Gas | Any | T 2 | T 44 |
| T 2 | 1200/500 @ 1Hz Sweeping - DIN / PFEER P.T.A.P. | Any | T 3 | T 44 |
| T 3 | 1000 @ 0.5Hz (1s on, 1s off) Intermittent - P... | Any | T 2 | T 44 |
| T 4 | 1.4KH-1.6KHz 1s, 1.6KHz-1.4KHz 0.5s - NF C 48... | Any | T 24 | T 1 |
| T 5 | 544(100mS)/440 (400mS) - NF S 32-001 | Any | T 19 | T 1 |
| T 6 | 1500/500 - (0.5s on , 0.5s off) x3 + 1s gap -... | Any | T 44 | T 1 |
| T 7 | 500-1500Hz Sweeping 2 sec on 1 sec off - AS4428 | Any | T 44 | T 1 |
| T 8 | 500/1200Hz @ 0.26Hz(3.3s on, 0.5s off) - NEN ... | Any | T 24 | T 35 |
| T 9 | 1000 (1s on, 1s off)x7 + (7s on, 1s off) - IM... | Any | T 34 | T 1 |
| T 10 | 1000 (1s on, 1s off)x7 + (7s on, 1s off) - IM... | Any | T 34 | T 1 |
| T 11 | 420(0.5s on, 0.5s off)x3 + 1s gap - ISO 8201 ... | Any | T 1 | T 8 |
| T 12 | 1000(0.5s on, 0.5s off)x3 + 1s gap - ISO 8201... | Any | T 1 | T 8 |
| T 13 | 422/775 - (0.85 on, 0.5 off) x3 + 1s gap - ... | Any | T 1 | T 8 |
| T 14 | 1000/2000 @ 1Hz - Singapore | Any | T 3 | T 35 |
| T 15 | 300 Continuous | Any | T 24 | T 35 |
| T 16 | 440 Continuous | Any | T 24 | T 35 |
| T 17 | 470 Continuous | Any | T 24 | T 35 |
| T 18 | 500 Continuous - IMO code 2 (Low) | Any | T 24 | T 35 |
| T 19 | 554 Continuous | Any | T 24 | T 35 |
| T 20 | 660 Continuous | Any | T 24 | T 35 |
| T 21 | 800 Continuous - IMO code 2 (High) | Any | T 24 | T 35 |
| T 22 | 1200 Continuous | Any | T 24 | T 35 |
| T 23 | 2000 Continuous | Any | T 3 | T 35 |
| T 24 | 2400 Continuous | Any | T 20 | T 35 |
| T 25 | 440 @ 0.83Hz (0.60s on, 0.60s off) Intermittent | Any | T 44 | T 8 |
| T 26 | 470 @ 0.9Hz (0.55s on, 0.55s off) Intermittent | Any | T 44 | T 8 |
| T 27 | 470 @ 5Hz (0.10s on, 0.10s off) Intermittent | Any | T 44 | T 8 |
| T 28 | 544 @ 1.14Hz (0.43s on, 0.44s off) Intermittent | Any | T 24 | T 8 |
| T 29 | 655 @ 0.875Hz (0.57s on, 0.57s off) Intermittent | Any | T 44 | T 8 |
| T 30 | 660 @ 0.28Hz (1.80s on, 1.80s off) Intermittent | Any | T 24 | T 8 |
| T 31 | 660 @ 3.3Hz (0.15s on, 0.15s off) Intermittent | Any | T 24 | T 8 |
| T 32 | 745 @ 1Hz (0.50s on, 0.50s off) Intermittent | Any | T 24 | T 8 |

| S 1 | Description | S 2 | S 3 | S 4 |
|---|---|---|---|---|
| T 33 | 800 (0.25s on, 1.00s off) Intermittent | Any | T 24 | T 8 |
| T 34 | 800 @ 2Hz (0.25s on, 0.25s off) - IMO code 3.... | Any | T 24 | T 8 |
| T 35 | 1000 @ 1Hz (0.50s on, 0.50s off) Intermittent | Any | T 24 | T 8 |
| T 36 | 2400 @ 1Hz (0.50s on, 0.50s off) Intermittent | Any | T 24 | T 8 |
| T 37 | 2900 @ 5Hz (0.10s on, 0.10s off) Intermittent | Any | T 24 | T 8 |
| T 38 | 363/518 @ 1Hz (0.50s / 0.50s) Alternating | Any | T 8 | T 19 |
| T 39 | 450/500 @ 2Hz (0.25s / 0.25s) Alternating | Any | T 8 | T 19 |
| T 40 | 554/440 @ 1Hz (0.50s / 0.50s) Alternating | Any | T 24 | T 19 |
| T 41 | 554/440 @ 0.65Hz (0.76s / 0.76s) Alternating | Any | T 8 | T 19 |
| T 42 | 561/760 @ 0.83Hz (0.60s / 0.60s) Alternating | Any | T 8 | T 19 |
| T 43 | 780/600 @ 0.96Hz (0.52s / 0.52s) Alternating | Any | T 8 | T 19 |
| T 44 | 800/1000 @ 2Hz (0.25s / 0.25s) Alternating | Any | T 24 | T 19 |
| T 45 | 970/800 @ 2Hz (0.25s / 0.25s) Alternating | Any | T 8 | T 19 |
| T 46 | 800/1000 @ 0.875Hz (0.57s / 0.57s) Alternating | Any | T 24 | T 19 |
| T 47 | 2400/2900 @ 2Hz (0.25s / 0.25s) Alternating | Any | T 24 | T 19 |
| T 48 | 500/1200 @ 0.3Hz (1.67s / 1.67s) Sweeping | Any | T 24 | T 12 |
| T 49 | 560/1055 @ 0.18Hz (2.73s / 2.73s) Sweeping | Any | T 24 | T 12 |
| T 50 | 560/1055 @ 3.3Hz (0.15s / 0.15s) Sweeping | Any | T 24 | T 12 |
| T 51 | 600/1250 @ 0.125Hz (4s / 4s) Sweeping | Any | T 24 | T 12 |
| T 52 | 660/1200 @ 1Hz (0.50s / 0.50s) Sweeping | Any | T 24 | T 12 |
| T 53 | 800/1000 @ 1Hz (0.50s / 0.50s) Sweeping | Any | T 24 | T 12 |
| T 54 | 800/1000 @ 7Hz (0.07s / 0.07s) Sweeping | Any | T 24 | T 12 |
| T 55 | 800/1000 @ 50Hz (0.01s / 0.01s) Sweeping | Any | T 24 | T 12 |
| T 56 | 2400/2900 @ 7Hz (0.07s / 0.07s) Sweeping | Any | T 24 | T 12 |
| T 57 | 2400/2900 @ 1Hz (0.50s / 0.50s) Sweeping | Any | T 24 | T 12 |
| T 58 | 2400/2900 @ 50Hz (0.01s / 0.01s) Sweeping | Any | T 24 | T 12 |
| T 59 | 2500/3000 @ 2Hz (0.25s / 0.25s) Sweeping | Any | T 24 | T 12 |
| T 60 | 2500/3000 @ 7.7Hz (0.65s / 0.65s) Sweeping | Any | T 24 | T 12 |
| T 61 | 800Hz Motor Siren | Any | T 24 | T 12 |
| T 62 | 1200Hz Motor Siren | Any | T 24 | T 12 |
| T 63 | 2400Hz Motor Siren | Any | T 24 | T 12 |
| T 64 | Simulated Bell | Any | T 21 | T 12 |



No liability is accepted for any consequence of the use of this document. The technical specification of this unit is subject to change without notice due to our policy of continual product development. All dimensions are approximate. This unit is sold subject to our standard conditions of sale, a copy of which is available on request.