# E2xBL2 Multi-function LED **Beacon & Status Light**



The hazardous location E2xBL2 LED beacon and status light is UL/cULs approved for Class I Div 2, Class II Div 2, Class I Zone 2/22 as well as IECEx and ATEX certified for Zone 2 and 22 applications.

The hazardous area E2xBL2 LED status light & beacon utilises an array of high power Cree® LED's, orientated to optimise visibility in any direction.

The beacon can be configured as a steady beacon for status indicator use, with a light output of up to 87 candela. Alternatively one of the five flashing modes, with a light output of up to 160 candela, may be used for warning applications. DC voltage versions feature three remotely selectable stages enabling multiple warnings to be signalled from one device. The UV stable colour filter enhances the light output and is field replaceable.

#### **Features**

- Very large termination area.
- Ingress protection IP66/67
- Choice of five flash rates: 1Hz, 1.5Hz, 2Hz, double and triple flash.
- High and low power Steady On modes
- Three remotely selectable stages/channels on DC versions.
- · Glass lens & Stainless Steel guard
- UV stable PC field replaceable lens colour filter
- Stainless steel fixings
- Dual cable entries
- Duplicate cable terminations (in & out for daisy-chain installations)
- Ratchet adjustable stainless steel 'U' bracket.
- UL Marine approved

### **Approvals**

• ATEX certificate: DEMKO 06 ATEX 0421554X

IECEx certficate: IECEx ULD 14.0012X

UL/cUL File ref: E245313

Ex EAC certified: EAC RU C-GB.AA71.B.00273/20

#### Coding

- ATEX / IECEx certification II 3G Ex ec IIC T4 Gc Ta -20°C to +55°C II 3D Ex tc IIIC T85°C Dc Ta -20°C to +55°C
- NEC Class / Zone ratings US Class I Zone 2 AEx eb IIC T4 Gc Ta -20°C to +55°C Zone 22 AEx tc IIIB T85°C Dc Ta -20°C to +55°C
- CEC Class / Zone ratings Canada Class I Zone 2 Ex ec IIC T4 Gc X Ta -20°C to +55°C Class I Zone 2 Ex ec IIC T4A Gc X Ta -20°C to +40°C Zone 22 Ex tc IIIC T85°C Dc X Ta -20°C to +55°C
- NEC & CEC Class / Division Ratings for US / Canada Class I Div 2 Group ABCD T4A Ta -20°C to +55°C Class II Div 2 Group FG T6 Ta -20°C to +55°C Class III Div 1 & 2 Ta -20°C to +55°C



























## Specification

Source:	Array of 4 x High Power Cree® LED's		
Modes:	1Hz flash (60 fpm) 1.5Hz flash (90 fpm) 2Hz flash (120 fpm) Double strike flash Triple strike flash High Power Steady Low Power Steady		
Eff. Intensity cd:	87 cd – High Power Steady		
Eff. Intensity cd:	160 cd - 1Hz flash		
Lens colours:	Amber, Blue, Clear, Green, Magenta, Red & Yellow		
Voltages DC:	24V dc (18-54V dc)		
Voltages AC:	115V ac; 230V ac		
Ingress protection:	IP rating per EN600790:IP64 IP rating per EN60529:IP66 Type rating per UL50E/NEMA250:4/4X/13		
Enclosure material:	UL94V0 GRP (PPS)		
Lens material:	Borosilicate glass dome with PC prismatic lens cover.		
Guard:	Stainless Steel dome guard as standard		
Cable entries:	Dual M20x1.5 or 1/2"NPT		
Terminals:	0.5 – 2.5mm² (20·14 AWG)		
Line monitoring:	Blocking diode included EOL can be factory fitted		
LED life:	60,000 hours		
Operating temp:	-20 to +55°C [-4° to +131°F]		
Storage temp:	-40 to +70°C [-40° to +158°F]		
Relative humidity:	90% at 20°C [68°F]		
Weight:	1.48kg/3.25lbs		
* All candela data	is representative of performance with clear lens at		

**Part Codes** 

Part Code:	Ident.:	Descriptions
		Description:
Product type:	E2xBL2	LED Beacon/Status Light
Voltage:	AC115	115V ac 50/60Hz
· ·	AC230	230V ac 50/60Hz
	DC024	24V dc (18-54Vdc)
Cable entries: [e]	А	M20x1.5 & ½" NPT
	В	M20x1.5 & M20x1.5
	С	½" NPT & ½" NPT
Stopping plug	N	Nylon
material: [m]		
Bracket & Guard &	1	304 A2 Stainless Steel
tag: [s]	2	316 A4 Stainless Steel
	3	304 A2 Stainless Steel & Equip. Tag
	4	316 A4 Stainless Steel & Equip. Tag
Version: [v]	A1	UL, cULs, IECEx & ATEX
Enclosure: [x]	В	Black
Lens colour: [y]	A, B, C	Amber, Blue, Clear
	G, M, R, Y	Green, Magenta, Red, Yellow
Accessories:	SP65-0001-A4	Pole Mount Bracket Kit St/St A4 (316)
	SP65-0003-A4	Sunshade - St/St A4 (316)

## **Current Consumption**

Version:	Voltage	Steady High Power:	Steady Low Power:	Flashing 1Hz:
24Vdc	18-54Vdc	240mA	134mA	110mA
115Vac 50/60Hz	+/-10%	95mA	78mA	90mA
230Vac 50/60Hz	+/-10%	48mA	37mA	45mA

## Multi-function patterns

Stage 1:	Stage 2:	Stage 3:
Steady High Power	Flashing 1Hz	Triple Strike
Steady Low Power	Flashing 1Hz	Triple Strike
Flashing 1Hz	2x Flash 2Hz	Triple Strike
Flashing 1.5Hz	Flashing 2Hz	Double Strike
Flashing 2Hz	Triple Strike	Triple Strike
Double Strike	Steady High Power	Triple Strike
Triple Strike	Flashing 2Hz	Double Strike
Note: Remote secon	nd and third stage on DC units only	6 Jan 2025

## E2S Warning Signals sales@e2s.com www.e2s.com

optimum voltage.