# D1xL2F 123dB(A) 25W Explosion Proof Speaker



The D1xL2F is a 25W PA loudspeaker with re-entrant flare horn. A high SPL in a robust Type 4/4X, IP66 marine grade, corrosion proof aluminium enclosure ensures suitability for all Class I & II Div 1 & Zone 1, 20 and 21 explosion proof applications.

The re-entrant flare horn is high impact, fire retardant thermoplastic and is field replaceable – the driver employs a standard  $1\ 3/8$ " -18 male thread coupling. All models have triple cable entries and duplicated terminals.

The large termination chamber and cover feature a threaded flameproof joint simplifying both installation and routine maintenance.

### **Features**

- Multiple transformer tappings
- Ratchet adjustable 316 stainless steel bracket
- Triple cable entries, duplicated cable terminations
- Robust marine grade aluminium enclosure
- UL 1480 Speakers for Fire Alarm and Signaling Systems,
- CAN/ULC-S541 Speakers for Fire Alarm and Signaling Systems

### **Approvals**

UL/cUL File ref: E230764

• IECEx certificate: IECEx ULD 19.0008X

ATEX certificate: DEMKO 19 ATEX 2141X

• CSFM listing: 7136-2279:0504

UKCA certificate: UL21UKEX2132X

INMETRO IEx 24.0158X

DNV certificate: TAA00003KC

## Coding

• NEC Class Div

Class I Div 1 Group ABCD T5 Ta -55°C to +85°C (T6 +60°C)

• CEC Class Div

Class I Div 1 Group ABCD T5 Ta -55°C to +75°C (T6 +60°C)

NEC Class Zone

Class I Zone 1 AEx db IIC T4 Gb Ta -55°C to +75°C (T5 +70°C) Zone 21 AEx tb IIIC T91°C Db Ta -55°C to +75°C

CEC Class Zone

Ex db IIC T4 Gb Ta -55°C to +75°C (T5 +70°C) Ex tb IIIC T91°C Db Ta -55°C to +75°C

• IECEx / ATEX

II 2G Ex db IIC T4 Gb Ta -55°C to +75°C (T5 +70°C, T6 +55°C) II 2D Ex db IIIC T98°C Db Ta -55°C to +75°C

Product version: D - NEC & CEC Class Div

Class II Div 1 Group FG T6 Ta -40°C to +70°C

Class III Div 1 Ta -40°C to +70°C

Zone 20 IIIB T6 Ta -40°C to +70°C

See product manual for full product specific coding.



























_							
Si	ne	CI	ıtı	C	ati	OI	n
~	$\sim$	v		•	uч	•	

Specification					
Product version A SPL:	104dB +/-3dB @ 1W @ 1m (Pink) 119dB +/-3dB @ 25W @ 1m (Rated) 123dB(A) @ 1m at 1.3Khz (Max)				
Product version D SPL:	89dB +/-3dB @ 1W @ 1m (Pink) 98dB +/-3dB @ 25W @ 1m (Rated) 108dB(A) @ 1m at 1.3Khz (Max)				
Rated power:	25 Watts RMS				
25/70v line tappings:	25W/12.5W/6W/2W/1W tappings 25V: z=196/392/816.67/1.225K/2.45K/4.9K Ohm 70V: z=25/50/104.17/156.25K/312.5K/625 Ohm				
70v line tappings:	25W/12.5W/6W/2W tappings z=196 Ohms/392 Ohms/816.67 Ohms/2.45K Ohms				
100v line tappings:	25W/12.5W/6W/2W tappings z=400 Ohms/800 Ohms/ 1.67K Ohms/5K Ohms				
Low impedance:	8 Ohm or 16 Ohm				
Q Factor:	3.1 @ 500Hz, 2.8 @ 1KHz, 6.4 @ 2KHz, 13.2 @ 4KHz, 13.8 @ 8KHz				
Directivity Index:	4.9 @ 500Hz, 4.5 @ 1KHz, 8.1 @ 2KHz, 11.2 @ 4KHz, 11.4 @ 8KHz				
Frequency range:	400Hz to 8000 Hz				
DC Line monitoring:	2.2µF Capacitor (Transformer ) 470µF Capacitor (Low impedance)				
Ingress protection:	EN60529: IP66/67 UL50E / NEMA250: 4/4X/3R/13				
Enclosure material:	Marine grade LM6 aluminium alloy				
Enclosure colour:	Red or Grey, custom colours available on request				
Enclosure finish:	Chromate & powder coated finish ISO 12944-6 CX, C5VH & C5H				
Cable entries:	1 × 1/2"NPT & 2 x M20 Thread adaptors available				
Stopping plugs:	Brass, Nickel Plated or Stainless Steel				
Terminals:	0.5-2.5mm² (20-14 AWG) Duplicated terminals				
Grounding stud:	M5				
Enclosure volume:	<2 litres				
Product version A Installation temp:	NEC: -55° to +85°C [-67° to +185°F] CEC/IECEx/ATEX: -55° to +75°C [-67° to +167°F]				
Product version D Installation temp:	NEC Class Div: -40° to +70°C [-40° to +158°F] NEC Class Zone, CEC Class Div/Zone: -55° to +75°C [-67° to +167°F]				
Storage temp:	-55° to +85°C [-67° to +185°F]				
Relative humidity:	95% – Additional tropicalisation is recommended for applications where both high relative humidity and high ambient temperatures exist				
MTBF V100/V070/V725:	630.69 years / 5,524,861 hours - MIL 217				
MTBF R008/R016:	830.22 years / 7,272,727 hours - MIL 217				
Weight:	100V, 70V, 25/70V line: 4.5kg/9.9lbs Low imp.: 4.2kg/9.1lbs				

# **Part Codes**

rant Codes				
Part Code:	Identifier	Description:		
Product type:	D1xL2	D1xL2 25W Loudspeaker		
Horn type:	F	Flare re-entrant horn		
Type:	V100 V070 V725 R008 R016	100V Line Transformer 70V Line Transformer 25V/70V Line Transformer 8 Ohm Low impedance 16 Ohm Low impedance		
Cable entries:[e]	A B C D F G Note:	$2 \times M20x1.5 mm \ \& \ 1 \times 1/2"NPT$ $2 \times 1/2"NPT$ - adaptors $2 \times 3/4"NPT$ - adaptors $2 \times M25x1.5 mm$ - adaptors $1 \times 3/4"NPT$ - adaptor $1 \times M25x1.5 mm$ - adaptor All entries, excluding thread adaptors, supplied with stopping plugs installed.		
Stopping plug/ adaptor material: [m]	B N S	Brass Nickel plated brass Stainless steel		
Bracket material: [s]	1 3	A4 316 Stainless Steel A4 316 St/St with Equip. Tag		
Product version: [v]	A D	UL, cUL, IECEx, ATEX, CSFM, INMETRO, DNV Class II - UL, cUL (excluding 100V & 25V/70V)		
Product option: [o]	1 X	Standard product Custom configuration – contact E2S		
Enclosure colour: [x]	R G S	Red Grey Special colour – contact E2S		
Accessories: SP65-0001-A4 SP65-0003-A4		Pole Mount Bracket Kit St/St A4 (316) Sunshade – St/St A4 (316)		





SCRAP VIEW IN DIRECTION 'A'