D2xL2F 124dB(A) 25W Hazardous Location Speaker



The D2xL2F is a 25W PA loudspeaker with re-entrant flare horn. A high SPL in a robust Type 4/4X, IP66 marine grade, corrosion proof aluminium enclosure ensures suitability for all Class I/II Div 2 and Zone 2 & 22 hazardous location applications.

The re-entrant flare horn is high impact, fire retardant thermoplastic and is field replaceable – the driver employs a standard $1\ 3/8$ " -18 male thread coupling. All models have triple cable entries and duplicated terminals.

The large termination chamber and cover feature a threaded flameproof joint simplifying both installation and routine maintenance.

Features

- Sound output up to 124dB
- Dual 25V/70V or 100V line transformer
- Multiple transformer tappings
- Field replaceable flare component
- Ratchet adjustable 316 stainless steel bracket
- Triple cable entries
- Robust marine grade aluminium enclosure
- Duplicated cable terminations
- UL 1480A (Ed 1) Speakers for Commercial and Professional Use
- CSA C22.2 No. 205 (Ed 3) Signal Equipment
- UL 1480 (Ed 6) Speakers for Fire Alarm and Signaling Systems,
- CAN/ULC-S541 (Ed 4) Speakers for Fire Alarm and Signaling

Approvals

- UL/cUL File ref: E230764
- IECEx certificate: IECEx ULD 19.0008X
- ATEX certificate: DEMKO 19 ATEX 2141X
- UKCA certificate: UL21UKEX2132X
- CSFM listing: 7136-2279:0503
- CCOE PESO
- DNV certificate: TAA00003KC

Coding

NEC/CEC Class Div

Class I Div 2 Group ABCD T3 Ta -55°C to +85°C (T3A: +80°C) Class I Div 2 Group ABCD T3B Ta -55°C to +65°C (T3C: +60°C) Class II Div 2 Group FG T4 Ta -55°C to +85°C Class III Ta -55°C to +85°C

NEC Class Zone

Class I Zone 2 AEx ec IIC T3 Gb Ta -55°C to +75°C Zone 22 AEx tc IIIC T119°C Dc Ta -55°C to +75°

CEC Class Zone
 Ex ec IIC T3 Gc -55°C to +75°C
 Ex tc IIIC T119°C Dc -55°C to +75°C

• IECEx / ATEX

II 2G Ex ec IIC T3 Gc Ta -55°C to +75°C
II 2D Ex tc IIIC T119°C Dc Ta -55°C to +75°C
See product manual for full product specific coding.























Specification			
Sound pressure level:	104dB +/-3dB @ 1W @ 1m (Pink) 119dB +/-3dB @ 25W @ 1m (Rated) 124dB(A) @ 1 m at 1.3Khz (Max)		
Rated power:	25 Watts RMS		
25/70v line tappings:	25W/12.5W/6W/2W/1W tappings 25V: z=196/392/816.67/1.225K/2.45K/4.9K Ohm 70V: z=25/50/104.17/156.25K/312.5K/625 Ohm		
100v line tappings:	: 25W/12.5W/6W/2W tappings z=400 Ohms/800 Ohms/ 1.67K Ohms/5K Ohms		
Low impedance:	8 Ohm or 16 Ohm		
Q Factor:	2.7 @ 500Hz, 3.0 @ 1KHz, 7.7 @ 2KHz, 14.7 @ 4KHz, 14.7 @ 8KHz		
Directivity Index:	4.4 @ 500Hz, 4.8 @ 1KHz, 8.8 @ 2KHz, 11.7 @ 4KHz, 11.7 @ 8KHz		
Frequency range:	400Hz to 8000 Hz		
DC Line monitoring:	2.2µF Capacitor (Transformer) 470µF Capacitor (Low impedance)		
Ingress protection:	EN60529: IP66/67 UL50E / NEMA250: 4/4X/3R/13		
Enclosure material:	Marine grade LM6 aluminium alloy		
Enclosure finish:	Chromate & powder coated finish ISO 12944-6 CX, C5VH & C5H		
Enclosure colour:	Red or Grey, custom colours available on request		
Cable entries:	$1 \times 1/2$ "NPT & 2 x M20 Thread adaptors available		
Stopping plugs:	Brass, Nickel Plated or Stainless Steel		
Terminals:	0.5-2.5mm² (20-14 AWG) Duplicated terminals		
Grounding stud:	M5		
Enclosure volume:	<2 litres		
Installation temp:	NEC/CEC: -55° to +80°C [-67° to +176°F] CEC/IECEx/ATEX: -55° to +75°C [-67° to +167°F]		
Storage temp:	-55° to +85°C [-67° to +185°F]		
Relative humidity:	99% - tropicalised/conformal coated electronics		
MTBF V100/V070/V725:	630.69 years / 5,524,861 hours - MIL 217		
MTBF R008/R016:	830.22 years / 7,272,727 hours - MIL 217		
Weight:	Transformer versions: 4.5kg/9.9lbs Low impedance version.: 4.2kg/9.1lbs		

Part Codes

Part Code:	Identifier: Description:		
Product type:	D2xL2	D2xL2 25W Loudspeaker	
Horn type:	F	Flare re-entrant horn	
Туре:	V100 V725 R008 R016	100V Line Transformer 25/70V Line Transformer 8 Ohm Low impedance 16 Ohm Low impedance	
Cable entries:[e]	A B C D F G Note:	$2 \times M20x1.5 mm \& 1 \times 1/2"NPT$ $2 \times 1/2"NPT - adaptors$ $2 \times 3/4"NPT - adaptors$ $2 \times M25x1.5 mm - adaptors$ $1 \times 3/4"NPT - adaptor$ $1 \times M25x1.5 mm - adaptor$ All entries, excluding thread adaptors, supplied with stopping plugs installed.	
Stopping plug/ adaptor material: [m]	B N S	Brass Nickel plated brass Stainless steel	
Bracket material: [s]	1 3 5	A4 316 Stainless Steel A4 316 St/St with Equip. Tag A4 316 St/St with Equip. Tag and Duty Label	
Product version: [v]	А	UL, cUL, ULC, IECEx, ATEX, PESO, DNV	
Product option: [o]	1 X	Standard product Custom configuration – contact E2S	
Enclosure colour: [x]	R G S	Red Grey Special colour – contact E2S	
Accessories: SP65-0001-A4 SP65-0003-A4		Pole Mount Bracket Kit St/St A4 (316) Sunshade – St/St A4 (316)	



